

## TECHNICAL DATA SHEET

<b>INTRODUCTION</b>	<p>AMCOR-RR is based on chloride free chemical &amp; additive solution in water degreasing, derusting and phosphatising agent for ferrous metals. It is applied on rusted steel surfaces to remove rust before application of any protective coating</p>										
<b>AREAS OF APPLICATION</b>	<ul style="list-style-type: none"> <li>• On re-bars during repairs to reinforced concrete structures.</li> <li>• Removes rust from tools, engine components, machine parts, fasteners</li> <li>• Maintenance of mild steel structures like tanks, water pipelines, shuttering plates and other corroded steel surfaces.</li> </ul>										
<b>FEATURES &amp; BENEFITS</b>	<ul style="list-style-type: none"> <li>• Chloride free - Contains no chloride hence no chance of enhancing further corrosion.</li> <li>• Economical - Cost effective because of good coverage.</li> <li>• Non-Corrosive - Safe to use on all metals, Non-Flammable.</li> <li>• Ease of application - Ready to use, easily applicable by brush.</li> <li>• Penetration &amp; effect - effective rust removal even from areas difficult to reach &amp; penetrate.</li> </ul>										
<b>PHYSICAL PROPERTIES</b>	<table> <tr> <td>Appearance</td> <td>: Pale yellow Liquid</td> </tr> <tr> <td>% Solid Content</td> <td>: 26 ± 1</td> </tr> <tr> <td>pH</td> <td>: 1.80 – 2.50</td> </tr> <tr> <td>Viscosity by B4 FC at 30°C[sec]</td> <td>: 12-15</td> </tr> <tr> <td>Specific Gravity</td> <td>: 1.04</td> </tr> </table>	Appearance	: Pale yellow Liquid	% Solid Content	: 26 ± 1	pH	: 1.80 – 2.50	Viscosity by B4 FC at 30°C[sec]	: 12-15	Specific Gravity	: 1.04
Appearance	: Pale yellow Liquid										
% Solid Content	: 26 ± 1										
pH	: 1.80 – 2.50										
Viscosity by B4 FC at 30°C[sec]	: 12-15										
Specific Gravity	: 1.04										
<b>COVERAGE</b>	<p>About 70 - 80 sq ft /kg</p>										
<b>PACKING</b>	<p>1, 5 and 20 kg HDPE containers. Do not keep it in metal containers.</p>										

**SHELF LIFE**

AMCOR - RR can be stored in packed condition for one year.

**SAFETY DATA**

**HEALTH HAZARD:** AMCOR - RR is lightly acidic in nature. It is recommended to take necessary precaution, which one would take while handling acids. Use rubber hand gloves, splash goggles etc. Direct contact with any part of the body, especially with eyes must be avoided. In case of contact or splash into eyes, wash with water immediately and consult a physician.

**FIRE HAZARD:** By itself it cannot catch fire. If comes in contact with alkali, heat and fumes can generated.

**DISCLAIMER**

This information is given to the best of our knowledge. There is no legally binding assurance of certain properties for a specific purpose. The customer is responsible for determining whether the product and Information provided here is appropriate for his use. It is the sole responsibility of the customer to ensure that any proprietary rights and existing laws and legislation are observed.

**ANUVI CHEMICALS LIMITED (AN ISO 9001: 2015 COMPANY)**

**Sales office:** 205/210/211, Narmada, Laxmi Industrial Premises,  
Pokharan Road No.1, Vartak Nagar, Thane - 400 606,  
Maharashtra. India.

**Tel.:** +91-22-25855379 / 25855714    **Website** [www.resikon.com](http://www.resikon.com)

